

FIG. 1




FIG.2




FIG. 3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10




FIG. 11





FIG.12



This cross-sectional view shows a mechanical assembly. A base member (1) supports a series of components. A curved member (2) is positioned above the base. A central component (3) is shown in two positions: a solid line position and a dashed line position. A component (4) is shown in a curved, bent position. A component (5a) is located on the left side. A component (6) is at the top left, with sub-components 6a and 6c. A component (8) is located in the center. A component (11) is at the top right. A component (3a) is at the far right. A component (63) is located in the center-right. A component (4a) is at the bottom center, with sub-components 4b and 4c. A component (3) is also labeled at the bottom right.

FIG.17




FIG.18




FIG.19






FIG.20





10/526337

FIG.22





FIG.23







FIG.25




10/526337

FIG.26

	CLEANSING LIMIT (A)	CONVEYANCE LIMIT (B)	EMBODIMENT (C)	PERFORMANCE LIMIT (D)	WATER SPLASHING LIMIT (E)
INVENTION	R1:0.3 R2:0.2 Z1:5.5	R1:0.6 R2:0.4 Z1:5.0	R1:1.1 R2:0.9 Z1:4.0	R1:1.9 R2:1.1 Z1:3.0	R1:2.3 R2:1.2 Z1:2.5
	—	17%:83%	33%:67%	50%:50%	—
	—	—	—	—	—
PRIOR ART	R1:1.3 Z1:4.7	R1:1.8 Z1:4.2	—	R1:3.0 Z1:3.0	—
	—	30%:70%	—	50%:50%	—
	—	—	—	—	—

FIG.27



[illegible]

FIG.29




FIG.30




FIG.31

